

## SUPER PLASTICIZER FLOWAID FT

Admixture for GRC Production

Product Name	Product Type	Uses
<b>FLOWAID FT</b>	<b>Polycarboxylic Polymer/Lignosulphonate</b>	<b>Super-plasticizing Admixture for Sprayed GRC</b>

### Uses

- Particularly suitable for sprayed premix and sprayed GRC
- Enables large water reductions to be made whilst retaining workability.

### Advantages

- High workability without segregation
- No retardation
- Up to 20% water reduction possible
- Can be used with acrylic polymer

### Method of Use

Dispense with mix water

### Dosage

0.5 – 1.5% by weight of cement – Confirm after trials

### Storage and Shelf Life

Minimum 1 year in sealed containers stored in dry warehouse conditions (5 –30°C)

**PROTECT FROM FROST**

### Properties

Appearance:	Brown Liquid
Specific Gravity:	1.06
Chloride content % w/w:	<1.10% Chloride Free
Effect on setting:	Little effect
Freezing point °C	+1°C
Suitability:	All Portland Cements

**SUPPLIED IN 25L, 200L AND 1000L IBC'S  
SUPPLIED BY FIBRE TECHNOLOGIES INTERNATIONAL**

### **For further information contact:**

Fibre Technologies International Limited  
Avonmouth Way  
Avonmouth  
Bristol BS11 9YA

☎: +44 (0)117 9825855  
Fax: +44 (0)117 9820060  
info@fibretech.org  
www.fibretech.org



MEMBERS OF THE INTERNATIONAL GLASSFIBRE REINFORCED CONCRETE ASSOCIATION