

Fleximould 50

Easily demould even the most complex shapes and lower the risk of damage to moulds and casting



Two-part polyurethane rubber for creating moulds

Uses

GRC Fleximould is a two-part polyurethane rubber with exceptional physical properties, formulated for ease of use in typical factory conditions.

Fleximould makes light work of demoulding even the most complex shapes and lowers the risk of damage to moulds and casting, resulting in less rejects and higher productivity. Moulds are dimensionally stable and able to withstand the daily rigours of casting, demoulding, and handling without damage.

Product Information

Product Type:	Polyurethane Rubber
Appearance:	Cream
Hardness Shore A:	50
Elongation at Break (%):	1000
Tear Strength (N/mm):	26.3
Specific Gravity:	1.10
Tensile Strength (MPa):	5.5
Storage & Shelf Life:	6 months if unopened and stored in dry conditions

Advantages

- Flexible
- Versatile
- High density
- Durable and hardwearing
- Easy to use
- High quality end product

Available in 25kg drums, or 800kg pallets (40 drums)
Minimum order size 50kg

Supplied by Fibre Technologies International

Technical Support

Fibre Technologies International Ltd

Avonmouth Way
Avonmouth
Bristol BS11 9YA
United Kingdom

- Tel: +44 (0) 117 982 5855
- Fax: +44 (0) 117 982 0060
- info@fibrettech.org
- www.fibrettech.org

